

5-20 Watts	24-45 Watts	50-65 Watts	70-100 Watts	120-140 Watts	150-180 Watts	200-250 Watts	300-350 Watts	400-600 Watts	650-3000 Watts	LED Drivers	Configurable	DIN Rail
<p><b>ECL05</b> • 5 Watts • 2" x 1" x 0.9" • Single Output • PCB / Chassis Mount • Class II</p>	<p><b>VCP24</b> • 24 Watts • 2.91" x 1.64" x 1" • Single Output • Class II • Low Cost</p>	<p><b>VCS50</b> • 50 Watts • 4.33" x 3.07" x 1.42" • Single Output • Convection-cooled • Low Cost</p>	<p><b>VCS70</b> • 70 Watts • 5.12" x 3.88" x 1.57" • Single Output • Convection-cooled • Low Cost</p>	<p><b>SDS120</b> • 120 Watts • 5" x 3.2" x 1.54" • Single &amp; Multi Outputs • Convection-cooled • Mechanical Options</p>	<p><b>ECP150</b> • 150 Watts • 4" x 2" x 1.2" • Single Output • Fan Supply • High Efficiency</p>	<p><b>BCC200</b> • 200 Watts • 9.21" x 4.96" x 1.9" • Single Output • Baseplate-cooled • Remote On/Off</p>	<p><b>SDF300</b> • 300 Watts • 5" x 3.2" x 1.5" • Single &amp; Multi Outputs • Fan Cover Options • Remote On/Off</p>	<p><b>CCH400/600</b> • 400/600 Watts • 8.43" x 4.02" x 1.69" • Single Output • Baseplate-cooled • -40°C to +70°C Op.Temp.</p>	<p><b>SHP/MHP650</b> • 650 Watts • 8" x 4" x 2.5" • Single Output • Remote On/Off • Mechanical Options</p>	<p><b>DLG50</b> • 50 Watts • 7.2" x 1.6" x 1.3" • Single Output • Up to 88% Efficiency • IP67</p>	<p><b>LP/LP MD</b> • 250-450 Watts • Single &amp; Multi Outputs • Low Profile 1U • Semi F47 Compliant • Isolated Outputs</p>	<p><b>DNR05-60</b> • 5 - 60 Watts • Up to 89% Efficiency • Single Output • Convection-cooled • DC Standby Versions</p>
<p><b>VCP05</b> • 5 Watts • 2.3" x 1.4" x 0.85" • Single Output • Class II • Low Cost</p>	<p><b>ECS25</b> • 25 Watts • 3" x 2" x 0.95" • Single Output • &lt;0.3W Standby Power • Class I &amp; II</p>	<p><b>ECM60</b> • 60 Watts • 4" x 2" x 1.2" • Single &amp; Multi Outputs • Class I &amp; II • Convection-cooled</p>	<p><b>VFT80</b> • 80 Watts • 4" x 2" x 1.1" • Single Output • Class I • Low Cost</p>	<p><b>CLC125</b> • 125 Watts • 4" x 2" x 1.2" • Single Output • Fan Output • Low Profile</p>	<p><b>LCL150</b> • 150 Watts • 7.55" x 3.74" x 1.97" • Single Output • Convection-cooled • Low Cost</p>	<p><b>PBM200</b> • 200 Watts • 7" x 4" x 1.5" • Single &amp; Multi Outputs • Remote On/Off • Mechanical Options</p>	<p><b>SMQ300</b> • 300 Watts • 8" x 4" x 2" • Single Output • Mechanical Options • Remote On/Off</p>	<p><b>FCM400</b> • 400 Watts • 6" x 4" x 1.93" • Single Output • Low Noise Fan • 5V Standby</p>	<p><b>HCP650/1000</b> • 650/1000 Watts • Single Output • Programmable Voltage • Programmable Current • Controls and Alarms</p>	<p><b>DLG75</b> • 75 Watts • 8.3" x 2.6" x 1.4" • Single Output • Up to 93% Efficiency • IP67</p>	<p><b>fleXPower</b> • 400-2500 Watts • Single &amp; Multi Outputs • Semi F47 Compliant • Extra Power at High Line • Isolated Outputs</p>	<p><b>DNR120-480</b> • 120 - 480 Watts • Up to 90% Efficiency • Single Output • Convection-cooled • DC Standby Versions</p>
<p><b>ECL10</b> • 10 Watts • 2" x 1" x 0.9" • Single Output • PCB / Chassis Mount • Class II</p>	<p><b>ECL25/30</b> • 25/30 Watts • 3" x 1.4" x 1" • Single &amp; Multi Outputs • Class II • PCB / Chassis Mount</p>	<p><b>SDS60</b> • 60 Watts • 5" x 3" x 1.32" • Single &amp; Multi Outputs • Class I • Non-Std O/P's Available</p>	<p><b>ECC100</b> • 100 Watts • 5" x 4.1" x 1.8" • Single Output • Baseplate-cooled • Remote On/Off</p>	<p><b>JPS130/M</b> • 130 Watts • 5" x 3" x 1.34" • Single &amp; Multi Outputs • Fan Output • Convection Rating</p>	<p><b>SDS150/M</b> • 150 Watts • 5" x 3.2" x 1.62" • Single Output • Convection-cooled • Mechanical Options</p>	<p><b>CCB250</b> • 250 Watts • 6" x 4" x 1.5" • Single Output • Convection-cooled • Efficiency up to 95%</p>	<p><b>LCL300</b> • 150 Watts • 8.07" x 4.33" x 1.97" • Single Output • Remote On/Off • Low Cost</p>	<p><b>SMM400</b> • 400 Watts • 9.1" x 4.2" x 2.5" • Single &amp; Multi Outputs • Current Share Option • SEMI F47 Compliant • Remote On/Off</p>	<p><b>SMR800</b> • 800 Watts • 9.1" x 4.2" x 2.5" • Single Output • SEMI F47 Compliant • Remote On/Off</p>	<p><b>DLG120</b> • 120 Watts • 8.7" x 2.6" x 1.4" • Single Output • Up to 92% Efficiency • IP67</p>	<p><b>MP</b> • 300-2400 Watts • Single &amp; Multi Outputs • SEMI F47 Compliant • Status Signals • Extra Power at High Line</p>	<p><b>DNR120-960</b> • 120 - 960 Watts • Up to 92% Efficiency • Three Phase Input • Single Output • Convection-cooled</p>
<p><b>ECL15</b> • 15 Watts • 2.5" x 1.25" x 0.96" • Single &amp; Multi Outputs • PCB / Chassis Mount • Class II</p>	<p><b>ECM40</b> • 40 Watts • 4" x 2" x 1.2" • Single &amp; Multi Outputs • Class I &amp; II • Convection-cooled</p>	<p><b>VCT60</b> • 60 Watts • 4" x 2" x 0.95" • Single Output • Class I • Low Cost</p>	<p><b>ECM100</b> • 100 Watts • 4.5" x 2.5" x 1.2" • Single &amp; Multi Outputs • Class I &amp; II • PoE Version</p>	<p><b>ECM140</b> • 140 Watts • 5" x 3" x 1.3" • Single Output • 120W Convection • Signals Options</p>	<p><b>VFT150</b> • 150 Watts • 6" x 5" x 1.34" • Single Outputs • Fan Output • Low Cost</p>	<p><b>CCM250</b> • 250 Watts • 6" x 4" x 1.54" • Single Output • Convection-cooled • 5V Standby</p>	<p><b>PBM300</b> • 300 Watts • 8" x 5" x 1.75" • Single &amp; Multi Outputs • Remote On/Off • Mechanical Options</p>	<p><b>SMQ400</b> • 400 Watts • 9.55" x 5.9" x 2.4" • Single Output • Mechanical Options • Remote On/Off</p>	<p><b>SHP/MHP1000</b> • 1000 Watts • 9.55" x 5.9" x 2.4" • Single Output • Remote On/Off • Screw Terminals</p>	<p><b>DLG150</b> • 150 Watts • 8.8" x 2.6" x 1.5" • Single Output • Up to 94% Efficiency • IP67</p>		
<p><b>VCP15</b> • 15 Watts • 2.55" x 1.49" x 1.09" • Single Output • Class II • Low Cost</p>	<p><b>ECE40</b> • 40 Watts • 3.2" x 1.5" x 1.1" • Single Output • PCB / Chassis Mount • Ultra Compact Size</p>	<p><b>ECS60</b> • 60 Watts • 3" x 2" x 1.05" • Single Output • &lt;0.5W Standby Power • Class I &amp; II</p>	<p><b>ECS100</b> • 100 Watts • 4" x 2" x 1.2" • Single Output • &lt;0.5W Standby Power • Class I &amp; II</p>	<p><b>ECL175</b> • 175 Watts • 5" x 3" x 1.3" • Single Output • Fan Output • Signals Options</p>	<p><b>EMH250</b> • 250 Watts • 5" x 3" x 1.43" • Single Output • Medical BF Compliant • 80-275 VAC Operation</p>	<p><b>SDC320</b> • 320 Watts • 6" x 4" x 2.14" • Single &amp; Multi Outputs • Status Signals • Remote On/Off</p>	<p><b>MFA420</b> • 420 Watts • 6.8" x 3.2" x 1.5" • Single Output • High Power Density • Active Current Share</p>	<p><b>GFR1K5</b> • 1500 Watts • 12.6" x 4" x 1.6" • Single Output • I<sup>2</sup>C Interface • Current Share &amp; Signals</p>				
<p><b>ECP20</b> • 20 Watts • 2.64" x 1.57" x 0.73" • Single &amp; Dual Output • Class II • PCB Mount</p>	<p><b>ECP40</b> • 40 Watts • 3" x 2" x 0.9" • Single &amp; Multi Outputs • Class I • Low Profile</p>	<p><b>ECP65</b> • 65 Watts • 3" x 2" x 1" • Single &amp; Multi Outputs • IT &amp; Medical Approvals • Peak Load Capacity</p>	<p><b>VCS100</b> • 100 Watts • 6.26" x 3.87" x 1.65" • Single Output • Convection-cooled • Low Cost</p>	<p><b>RCL175</b> • 175 Watts • 6.26" x 3.7" x 1.38" • Single &amp; Multi Outputs • Class I &amp; II • Mechanical Options</p>	<p><b>SDR250</b> • 250 Watts • 5" x 3.2" x 1.5" • Single &amp; Multi Outputs • Fan Cover Options • Remote On/Off</p>	<p><b>EMH350</b> • 350 Watts • 9.8" x 3" x 1.43" • Single Output • Medical BF Compliant • Analog &amp; PMBus Opt.</p>	<p><b>LCL500</b> • 500 Watts • 9.8" x 3" x 1.43" • Single Output • Remote On/Off • Low Cost</p>	<p><b>HPU1K5</b> • 1500 Watts • 12.8" x 4" x 1.7" • Single Output • Current Share • Status Signals</p>				
<p><b>ECE20</b> • 20 Watts • 2.06" x 1.07" x 0.91" • Single Output • PCB Mount • Ultra Compact Size</p>	<p><b>ECS45</b> • 45 Watts • 3" x 2" x 0.95" • Single Output • &lt;0.3W Standby Power • Class I &amp; II</p>	<p><b>ECS65</b> • 65 Watts • 4" x 2" x 1.54" • Single Output • &lt;0.5W Standby Power • Low Leakage Current</p>		<p><b>SDS180</b> • 180 Watts • 5" x 3.21" x 1.54" • Convection-cooled • Mechanical Options</p>	<p><b>MFA350</b> • 350 Watts • 6.8" x 3.2" x 1.5" • Single Output • Fan Cover Options • Remote On/Off</p>	<p><b>SMC500/600</b> • 500/600 Watts • 8" x 4.33" x 2.5" • Single Output • Remote On/Off • Current Share Options</p>	<p><b>HCP1500/3000</b> • 1500/3000 Watts • Single Output • Programmable Voltage • Programmable Current • Controls and Alarms</p>					

= Green Power = Medical Versions Available